

Order number: 02 806 06 99

## SCHELL urinal control EDITION E

battery operation 6 V

Suitable for connection with SWS, capable of parameterised by SSC.

### Scope of delivery:

- contactless infrared sensor flushing unit
- electronic module programmable
- mounting frame
- front panel with sensor window
- bistable cartridge solenoid valve 6 V
- battery compartment 6 V
- 4 x 1,5 V alkaline batteries type AA

### Field of application / Technical data:

- adjustable by means of short range reflex
  - flush time: 1 - 15 s, adjustable
  - sensor range: short, medium, Long
  - Stagnation flush program: Off/ 30 s, every 24 h after last use / every 24 h)
  - pre-flush: Off, On 1 s
  - automatical stadium program: Off, On
  - odour trap flush: Off, On
- expanded setting options with SWS/SSC
  - flush time: 1 - 15 s, adjustable
  - sensor range: short, medium, Long
  - Stagnation flush program: 24 h after last use / every 24 h (adjustable 1 - 240 h) flush time: 30 s (adjustable 5 - 600 s)
  - pre-flush: 1 s (adjustable 5 - 60 min after last use)
  - automatical stadium program: 1 s/user (adjustable 20-60 s after last use)
  - odour trap flush: Off, On (adjustable 1 - 240 h after last use)
  - energy-saving mode: active after 1 h (adjustable: off, 1 h - 254)

### Details:

- Material: front cover out of plastic
- Surface: chrome
- Weight: 0.57 kg/pc.
- Packaging unit: 1

### Versions:

alpine white, PU 1, W: 0.57 kg/pc.

Order No.: [02 806 15 99](#)

vandal-resistant design, stainless steel, PU 1, W: 0.64 kg/pc.

Order No.: [02 807 28 99](#)

### Required associated item:

concealed urinal flush valve COMPACT II

Order No.: [01 193 00 99](#) or

urinal-module MONTUS

Order No.: [03 075 00 99](#) or

SSC USB-adapter

Order No.: [01 586 00 99](#)