

Order number: 02 806 15 99

SCHELL urinal control EDITION E

battery operation 6 V

Suitable for connection with SWS, capable of parameterised by SSC.

Scope of delivery:

- contactless infrared sensor flushing unit
- electronic module programmable
- mounting frame
- front panel with sensor window
- bistable cartridge solenoid valve 6 V
- battery compartment 6 V
- 4 x 1,5 V alkaline batteries type AA

Field of application / Technical data:

- adjustable by means of short range reflex
 - flush time: 1 - 15 s, adjustable
 - sensor range: short, medium, Long
 - Stagnation flush program: Off/ 30 s, every 24 h after last use / every 24 h)
 - pre-flush: Off, On 1 s
 - automatical stadium program: Off, On
 - odour trap flush: Off, On
- expanded setting options with SWS/SSC
 - flush time: 1 - 15 s, adjustable
 - sensor range: short, medium, Long
 - Stagnation flush program: 24 h after last use / every 24 h (adjustable 1 - 240 h) flush time: 30 s (adjustable 5 - 600 s)
 - pre-flush: 1 s (adjustable 5 - 60 min after last use)
 - automatical stadium program: 1 s/user (adjustable 20-60 s after last use)
 - odour trap flush: Off, On (adjustable 1 - 240 h after last use)
 - energy-saving mode: active after 1 h (adjustable: off, 1 h - 254)

Details:

- Material: front cover out of plastic
- Surface: alpine white
- Weight: 0.57 kg/pc.
- Packaging unit: 1

Versions:

chrome, PU 1, W: 0.57 kg/pc.

Order No.: [02 806 06 99](#)

vandal-resistant design, stainless steel, PU 1, W: 0.64 kg/pc.

Order No.: [02 807 28 99](#)

Required associated item:

concealed urinal flush valve COMPACT II

Order No.: [01 193 00 99](#) or

urinal-module MONTUS

Order No.: [03 075 00 99](#) or

SSC USB-adapter

Order No.: [01 586 00 99](#)