

SPECIFICATION SHEET

TEHNIČKI LIST



STOLZ

COLLECTION
SERIJA

S3

PRODUCT CODE
ŠIFRA PROIZVODA

331601B



TEHNIČKI PODACI

Jednoručna baterija
Moderan dizajn
Telo od mesinga
Matt Black završna obrada
Ugradnja u zid
Tuš ruža D.255mm - PTRUSP33D
Termostatski uložak AP Thermo
DARKFLEX tuš crevo 150cm - PGC150DF
Tuš ručica - PTREC6D

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Modern design
Solid brass body
Matt Black finish
Build-in wall solution
Shower head D.255mm - PTRUSP33D
Theromostatic cartridge AP Thermo
DARKFLEX shower hose 150cm - PGC150DF
Hand shower - PTREC6D

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs
www.rosan.rs

ROSAN