

SPECIFICATION SHEET

TEHNIČKI LIST



STOLZ

COLLECTION
SERIJA

S3

PRODUCT CODE
ŠIFRA PROIZVODA

331701



TEHNIČKI PODACI

Jednoručna baterija

Moderan dizajn

Telo od mesinga

Hromirana završna obrada

Ugradnja u zid

Tuš ruža D.255mm - PTRUSP33

Termostatski uložak AP Thermo

SILVERFLEX tuš crevo 170cm - PGC170SF

Tuš ručica - PTREC6

TECHNICAL DETAILS

Single lever mixer

Modern design

Solid brass body

Chrome finish

Build-in wall solution

Shower head D.255mm - PTRUSP33

Thermostatic cartridge AP Thermo

SILVERFLEX shower hose 170cm - PGC170SF

Hand shower - PTREC6

RADNI USLOVI

Maksimalni radni pritisak: 5 bar

Preporučeni radni pritisak: 3 bar

Minimalni radni pritisak: 1 bar

Maksimalna dozvoljena temperatura: 70°C

Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar

Suggested working pressure : 3 bar

Min. working pressure : 1 bar

Max. working temperature : 70°C

Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

ROSAN