

SPECIFICATION SHEET

TEHNIČKI LIST



STOLZ

COLLECTION
SERIJA

S3

PRODUCT CODE
ŠIFRA PROIZVODA

333101B



TEHNIČKI PODACI

Jednoručna baterija
Moderan dizajn
Telo od mesinga
Hromirana završna obrada
Zidna montaža
Keramički mešač Hydroplast FA 35mm - **PKM35OPF**
Keramički prebacivač CITEC® **PKM27S3**
DARKFLEX tuš crevo 150cm - **PGC150DF**
Tuš ručica - **PTREC6D**

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Modern design
Solid brass body
Chrome finish
Wall fixing
Hydroplast FA 35 mm ceramic cartridge - **PKM35OPF**
Ceramic diverter CITEC® **PKM27S3**
DARKFLEX shower hose 150cm - **PGC150DF**
Hand shower - **PTREC6D**

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C