

# SPECIFICATION SHEET

## TEHNIČKI LIST



# STOLZ

COLLECTION  
SERIJA

# S4

PRODUCT CODE  
ŠIFRA PROIZVODA

# 431401



### TEHNIČKI PODACI

Jednoručna baterija

Moderan dizajn

Telo od mesinga

Hromirana završna obrada

Ugradnja u zid

NEOPERL® PERLATOR® Coin Slot PCA® PPM21CS

Keramički mešač KEROX 35mm Progressiv PKM35APR

### TECHNICAL DETAILS

Single lever mixer

Modern design

Solid brass body

Chrome finish

Build-in wall solution

NEOPERL® PERLATOR® Coin Slot PCA® PPM21CS

KEROX 35 mm ceramic cartridge progressiv PKM35APR

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar

Preporučeni radni pritisak: 3 bar

Minimalni radni pritisak: 1 bar

Maksimalna dozvoljena temperatura: 70°C

Preporučena temperatura vode: 50°C

### WORKING CONDITIONS

Max. working pressure : 5 bar

Suggested working pressure : 3 bar

Min. working pressure : 1 bar

Max. working temperature : 70°C

Suggested max. water temperature : 50°C

email : [info@rosan.rs](mailto:info@rosan.rs)

[www.rosan.rs](http://www.rosan.rs)

# ROSAN