

SPECIFICATION SHEET

TEHNIČKI LIST



STOLZ

COLLECTION
SERIJA

S4

PRODUCT CODE
ŠIFRA PROIZVODA

439101



TEHNIČKI PODACI

Jednoručna baterija

Moderan dizajn

Telo od mesinga

Hromirana završna obrada

Fiksiranje na jedan otvor

NEOPERL® HONEYCOMB® - PPM22N

Keramički mešač Hydroplast 25mm GX25

Set za pričvršćenje sa jednim vijkom

NEOPERL® SPX® priključna creva - FB50PX

Pokretni izliv

TECHNICAL DETAILS

Single lever mixer

Modern design

Solid brass body

Chrome finish

Single hole assembly

NEOPERL® HONEYCOMB® - PPM22N

Hydroplast 25 mm ceramic cartridge GX25

Single screw fixing set

NEOPERL® SPX® connecting hoses - FB50PX

Swivel spout

RADNI USLOVI

Maksimalni radni pritisak: 5 bar

Preporučeni radni pritisak: 3 bar

Minimalni radni pritisak: 1 bar

Maksimalna dozvoljena temperatura: 70°C

Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar

Suggested working pressure : 3 bar

Min. working pressure : 1 bar

Max. working temperature : 70°C

Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

ROSAN