

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

BLAU

PRODUCT CODE
ŠIFRA PROIZVODA

B138100



TEHNIČKI PODACI

Jednoručna baterija
Montiranje na jedan otvor
Klasa protoka C
NEOPERL® PERLATOR® COIN SLOT®
Keramički mešač Blau A
INOX set za pričvršćenje
TUCAI TAQ fleksibilna priključna creva

TECHNICAL DETAILS

Single lever mixer
Single hole mounted
Flow class C
Aerator NEOPERL® PERLATOR® COIN SLOT®
Ceramic cartridge Blau A
Stainless Steel rapid instalation set
TUCAI TAQ flexible connection hoses

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

