

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

Gee.O

PRODUCT CODE
ŠIFRA PROIZVODA

JG30101



TEHNIČKI PODACI

Jednoručna baterija
Montiranje na jedan otvor
Klasa protoka 1,5gpm (5.4 lit/min)
NEOPERL® PERLATOR® Coin Slot PCA®
Keramički mešač KEROX® 35 HWS
Set za pričvršćenje sa jednim vijkom
NEOPERL® SPX® priključna creva

TECHNICAL DETAILS

Single lever mixer
Single hole assembly
Flow rate 1,5gpm (5.4 lit/min)
NEOPERL® PERLATOR® Coin Slot PCA®
Ceramic cartidge KEROX® HWS 35 mm
Single screw fixing set
NEOPERL® SPX® flexible hoses

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C