

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

Gee.O

PRODUCT CODE
ŠIFRA PROIZVODA

JG31701



TEHNIČKI PODACI

Jednoručna baterija
Montaža u zidu
Klasa protoka C - na izlivu
Regulacija protoka do 5 lit/min na tušu
Keramički mešač KEROX® 35 HWS
Rozeta u ravni sa zidom
Automatski prebacivač za tuš na telu
Automatski prebacivač na izlivu
Konzola tuša L. 400mm
Zglobna tuš ruža D. 200mm
Tuš ručica 3 Funkcije
Gun metal tuš crevo 1.5m

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Built-in wall
Flow class C - on spout
Flow regulation on shower up to 5 lit/min
Ceramic cartridge KEROX® 35 HWS
Minimalistic rossete
Automatic shower diverter on mixer body
Automatic diverter on the spout
Shower colum L. 400mm
Shower head D. 220mm
3 Function hand shower
Gun metal shower hose 1.5m

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

ROSAN