

LIS

Flush plate AW1, dual flush



DIMENSIONS

Length	250 mm
Width	10 mm
Height	160 mm

COLOUR AND FINISH

■ 716 Plastic with black matt finish

OPTIONS

000 - standard option

SPECIFICATION TEXT

Frontal activation, actuation force below 25 N.

Net weight (kg) : 0.35

Number of buttons : 2

COMPATIBLE WITH



Installation system LIS CW1 with cistern for wall-hung WC, dual flush 6/3L (adjustable to 4.5/3L)

H8946600000001



Installation system LIS CW2 with cistern for wall-hung WC and shower toilet, dual flush 6/3L (adjustable to 4.5/3L)

H8946610000001



Freestanding installation system LIS CW3 with cistern for wall-hung WC, dual flush 6/3L (adjustable to 4.5/3L)

H8946620000001



Installation system LIS TW1 for brick wall installation with cistern for wall-hung WC, dual flush 6/3L (adjustable to 4.5/3L)

H8946630000001



Concealed cistern for wall-hung WC and floorstanding WC pan, dual flush 6/3L (adjustable to 4.5/3L)

H8946640000001



Concealed frame with cistern for wall-hung WC, Dual Flush 4.5/3L (adjustable to 6/3L)

H8946650000001



Installation system LIS CW2 with cistern for wall-hung WC and shower toilet, dual flush 4.5/3L (adjustable to 6/3L)

H8946660000001





04768803bac35d153bf3e09cddb3b319

LIS

The LAUFEN installation system LIS is the perfect solution for safely, quickly and easily installing LAUFEN's wall-hung toilets. The range includes various concealed elements for dry and wet construction, and makes a wide variety of different installation scenarios realisable. All wall mounted units are equipped with a toilet tank that has a water-saving dual flush system, meaning flushing options can be set to either 6/3 litres or 4.5/3 litres.