

# SPECIFICATION SHEET

## TEHNIČKI LIST



COLLECTION  
SERIJA

# BRONTEE

PRODUCT CODE  
ŠIFRA PROIZVODA

**NB10251**



### TEHNIČKI PODACI

Dvoručna baterija  
Zidna montaža  
Flühs® LIFETIME keramički gornji delovi  
Metalni rukohvat  
Podesivi usponski tuš  
Specijalna Brontee završna obrad  
Zglobna tuš ruža metalna D. 200mm  
Duplo pleteno tuš crevo 1.5m  
Metalna tuš ručica  
Heavy Duty ekscentar kolena

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Two handle mixer  
Wall mounted  
Flühs® LIFETIME ceramic head parts  
Metal handle  
Adjustable height stand pipe shower  
Special Brontee finish  
Metal Shower head D. 200mm  
Double lock shower hose 1.5m  
Solid brass hand shower  
Heavy Duty eccentric connectors

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C

email : [info@rosan.rs](mailto:info@rosan.rs)

[www.rosan.rs](http://www.rosan.rs)

