

PE0 18/21/24

CONVENIENCE INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 233991

The main features

Accurate temperature delivery up to the maximum output

High energy efficiency - 30 % savings possible









Туре	PEO 18/21/24	PEO 27
Part no.	233991	233992
Rated output	18/21/24 kW	27 kW
Height	485 mm	485 mm
Width	226 mm	226 mm
Depth	93 mm	93 mm

Technical data

Rated voltage 1	380 V	380 V
Rated output 1	16,2/19/21,7 kW	24,4 kW
Rated current 1	27,6/29,5/33,3 A	37,1 A
Fuse 1	32/32/35 A	40 A
Frequency 1	50/60 Hz	50/60 Hz
Rated voltage 2	400 V	400 V
Rated output 2	18/21/24 kW	27 kW
Rated current 2	29/31/35 A	39 A
Fuse 2	32/32/35 A	40 A
Frequency 2	50/60 Hz	50/60 Hz
Rated voltage 3	415 V	
Rated output 3	19,4/22,6/25,8 kW	
Rated current 3	30,1/32,2/36,3 A	
Fuse 3	32/32/40 A	
Frequency 3	50/- Hz	
Phases	3/PE	3/PE
Temperature adjustment	30-60 °C	30-60 °C
Specific resistance ρ15 ≥ (at tcold ≤25 °C and 380 V)	900 Ω cm	900 Ω cm



Specific conductivity σ15 ≤ (at ϑcold ≤25 °C and 380 V)	1111 μS/cm	1111 μS/cm
Specific resistance ρ15 ≥ (at ઉcold ≤25 °C and 400 V)	900 Ω cm	900 Ω cm
Specific conductivity σ 15 ≤ (at ϑ cold ≤25 °C and 400 V)	1111 μS/cm	1111 μS/cm
Specific resistance ρ15 ≥ (at ઉcold ≤45 °C and 380 V)	1200 Ω cm	1200 Ω cm
Specific conductivity σ15 ≤ (at ϑcold ≤45 °C and 380 V)	833 μS/cm	833 μS/cm
Specific resistance ρ15 ≥ (at ઉcold ≤45 °C and 400 V)	1200 Ω cm	1200 Ω cm
Specific conductivity σ15 ≤ (at ϑcold ≤45 °C and 400 V)	833 µS/cm	833 μS/cm
Energy efficiency class	А	А
IP-Rating	IP25	IP25
Colour	white	white
Weight	3,6 kg	3,6 kg



Contact information

You have questions? We appreciate to help you: Call +49 5531 - 7020 Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.