

HL0317.1E

stainless steel grate 138x138mm



TECHNICAL DATA

material	Edelstahl	installation height	
dimension	138 x 138 mm	grate frame	
capacity		grate	
weight	0,208	load class	K - 300 kg
EAN	9003076317011	inlet	
		standards	

MAIN DATA

used with



HL66.3
grating d 145mm sleek/147x147mm/138x138mm



HL317
floor drain DN50/75/110 vertical 147x147mm/138x138mm



HL317H
floor drain DN50/75/110 vertical with bitumen membrane, 147x147mm/138x138mm



HL72.1HN
floor drain DN75/110 horizontal with bitumen membrane, 147x147mm/138x138mm

**HL72.1N**

floor drain DN75/110 horizontal with flange, 147x147mm/138x138mm

**HL66.9**

grating d 145mm fluted/148x148mm/138x138mm

**HL62.1B/1**

flat-roof drain DN110 with clamping ring, heated (10-30W/230V). Walkable - 148x148mm/137x137mm

**HL62.1B/2**

flat-roof drain DN125 with clamping ring, heated (10-30W/230V). Walkable - 148x148mm/137x137mm

**HL62.1B/5**

flat-roof drain DN160 with clamping ring, heated (10-30W/230V). Walkable - 148x148mm/137x137mm

**HL62.1B/7**

flat-roof drain DN75 with clamping ring, heated (10-30W/230V). Walkable - 148x148mm/137x137mm

**HL62.1BF/1**

Flat-roof drain DN110 vertical with PP-flange and heating /10-30W/230V), walkable

**HL62.1BF/2**

Flat-roof drain DN125 vertical with PP-flange and heating /10-30W/230V), walkable

**HL62.1BF/7**

Flat-roof drain DN75 vertical with PP-flange and heating /10-30W/230V), walkable

**HL62.1BH/1**

flat-roof drain DN110 with bitumen membrane, heated (10-30W/230V). Walkable - 148x148mm/137x137mm

**HL62.1BH/2**

flat-roof drain DN125 with bitumen membrane, heated (10-30W/230V). Walkable - 148x148mm/137x137mm

**HL62.1BH/5**

flat-roof drain DN160 with bitumen membrane, heated (10-30W/230V). Walkable - 148x148mm/137x137mm

**HL62.1BH/7**

flat-roof drain DN75 with bitumen membrane, heated (10-30W/230V). Walkable - 148x148mm/137x137mm

**HL62.1BP/1**

flat-roof drain DN110 with PVC collar, heated (10-30W/230V). Walkable - 148x148mm/137x137mm

**HL62.1BP/2**

flat-roof drain DN110 with PVC collar, heated (10-30W/230V). Walkable - 148x148mm/137x137mm

**HL62.1BP/5**

flat-roof drain DN160 with PVC collar, heated (10-30W/230V). Walkable - 148x148mm/137x137mm

**HL62.1BP/7**

flat-roof drain DN75 with PVC collar, heated (10-30W/230V). Walkable - 148x148mm/137x137mm

**HL62B/1**

flat-roof drain DN110 with clamping ring. Walkable - 148x148mm/137x137mm

**HL62B/2**

flat-roof drain DN125 with clamping ring. Walkable - 148x148mm/137x137mm

**HL62B/5**

flat-roof drain DN160 with clamping ring. Walkable - 148x148mm/137x137mm

**HL62B/7**

flat-roof drain DN75 with clamping ring. Walkable - 148x148mm/137x137mm

**HL62BF/1**

Flat-roof drain DN110 vertical with PP-flange, walkable. Frame 137mm x 137mm, grate 148mm x 148mm.

**HL62BF/2**

Flat-roof drain DN125 vertical with PP-flange, walkable. Frame 137mm x 137mm, grate 148mm x 148mm.

**HL62BF/7**

Flat-roof drain DN75 vertical with PP-flange, walkable. Frame 137mm x 137mm, grate 148mm x 148mm.

**HL62BH/1**

flat-roof drain DN110 with bitumen membrane. Walkable - 148x148mm/137x137mm

**HL62BH/2**

flat-roof drain DN125 with bitumen membrane. Walkable - 148x148mm/137x137mm

**HL62BH/5**

flat-roof drain DN160 with bitumen membrane. Walkable - 148x148mm/137x137mm

**HL62BH/7**

flat-roof drain DN75 with bitumen membrane. Walkable - 148x148mm/137x137mm

**HL62BP/1**

flat-roof drain DN110 with PVC collar. Walkable - 148x148mm/137x137mm

**HL62BP/2**

flat-roof drain DN125 with PVC collar. Walkable - 148x148mm/137x137mm

**HL62BP/5**

flat-roof drain DN160 with PVC collar. Walkable - 148x148mm/137x137mm

**HL62BP/7**

flat-roof drain DN75 with PVC collar. Walkable - 148x148mm/137x137mm

**HL64.1B**

flat-roof drain DN75/110 horizontal with clamping ring heated (10-30W/230V). Walkable - 148x148mm/137x137mm

**HL64.1BF/1**

Flat-roof drain DN110 horizontal with PP-flange and heating /10-30W/230V), walkable

**HL64.1BF/7**

Flat-roof drain DN75 horizontal with PP-flange and heating /10-30W/230V), walkable

**HL64.1BH**

flat-roof drain DN75/110 horizontal with bitumen membrane heated (10-30W/230V). Walkable - 148x148mm/137x137mm

**HL64.1BP/1**

Flat-roof drain DN110 horizontal with PVC-flange and heating /10-30W/230V), walkable

**HL64.1BP/7**

Flat-roof drain DN75 horizontal with PVC-flange and heating /10-30W/230V), walkable

**HL64B**

flat-roof drain DN75/110 horizontal with clamping ring. Walkable - 148x148mm/137x137mm

**HL64BF/1**

Flat-roof drain DN110 horizontal with PP-flange, walkable. Frame 137mm x 137mm, grate 148mm x 148mm.

**HL64BF/7**

Flat-roof drain DN75 horizontal with PP-flange, walkable. Frame 137mm x 137mm, grate 148mm x 148mm.

**HL64BH**

flat-roof drain DN75/110 horizontal with bitumen membrane. Walkable - 148x148mm/137x137mm

**HL64BP/1**

Flat-roof drain DN110 horizontal with PVC-flange, walkable. Frame 137mm x 137mm, grate 148mm x 148mm.

**HL64BP/7**

Flat-roof drain DN75 horizontal with PVC-flange, walkable. Frame 137mm x 137mm, grate 148mm x 148mm.

**HL72N**

basement drain DN110 horizontal 148x148mm/138x138mm

**HL72N/7**

basement drain DN75 horizontal 148x148mm/138x138mm

**HL66P**

grating d 145mm sleek with PVC collar 206x206mm/138x138mm

DOWNLOADS

Foto Print	HL0317_1E_pr.tif	max.
Foto Web	HL0317_1E_B.jpg	640x480/300dpi
Foto Parts List	HL0317_1E_gr.jpg	150x150/72dpi