

# EIL 4 Trend

MINI INSTANTANEOUS WATER HEATERS

PRODUCT-NO.: 200143

## The flexible way to freshen up

**Adapted to your needs** Do you want a reliable supply of hot water to your hand washbasin without wasting energy? Then choose this mini instantaneous water heater. Its direct connection to the tap and fast bare wire heating system ensure that DHW is available for you immediately.

## The main features

Mini instantaneous water heater with hydraulic control for small amounts of hot water available immediately

---

Flexible installation thanks to undersink or oversink installation

---

Operation with non-pressurised tap

---

Special aerator for perfect flow pattern



**EIL 3 Trend**

Product-No.: 200142

---



**EIL 6 Trend**

Product-No.: 200144



| Type     | EIL 3 Trend | EIL 4 Trend | EIL 6 Trend |
|----------|-------------|-------------|-------------|
| Part no. | 200142      | 200143      | 200144      |

## Technical data

|                   |          |          |          |
|-------------------|----------|----------|----------|
| Rated voltage     | 230 V    | 230 V    | 230 V    |
| Rated voltage 1   | 200 V    | 200 V    | 200 V    |
| Rated voltage 2   | 220 V    | 220 V    | 220 V    |
| Rated voltage 3   | 230 V    | 230 V    | 230 V    |
| Rated voltage 4   | 240 V    | 240 V    | 240 V    |
| Rated output      | 3,53 kW  | 4,4 kW   | 5,7 kW   |
| Rated output 1    | 2,7 kW   | 3,3 kW   | 4,3 kW   |
| Rated output 2    | 3,2 kW   | 4,0 kW   | 5,2 kW   |
| Rated output 3    | 3,53 kW  | 4,4 kW   | 5,7 kW   |
| Rated output 4    | 3,8 kW   | 4,8 kW   | 6,2 kW   |
| Rated current     | 15,2 A   | 19,1 A   | 24,7 A   |
| Rated current 1   | 13,3 A   | 16,7 A   | 21,6 A   |
| Rated current 2   | 14,5 A   | 18,2 A   | 23,6 A   |
| Rated current 3   | 15,2 A   | 19,1 A   | 24,7 A   |
| Rated current 4   | 15,8 A   | 20 A     | 25,8 A   |
| Fuse protection   | 16 A     | 20 A     | 25 A     |
| Fuse protection 1 | 16 A     | 20 A     | 25 A     |
| Fuse protection 2 | 16 A     | 20 A     | 25 A     |
| Fuse protection 3 | 16 A     | 20 A     | 25 A     |
| Fuse protection 4 | 16 A     | 20 A     | 32 A     |
| Frequency         | 50/60 Hz | 50/60 Hz | 50/60 Hz |

|  |                      |                      |                      |
|--|----------------------|----------------------|----------------------|
| Frequency 1  | 50/60 Hz             | 50/60 Hz             | 50/60 Hz             |
| Frequency 2  | 50/60 Hz             | 50/60 Hz             | 50/60 Hz             |
| Frequency 3  | 50/60 Hz             | 50/60 Hz             | 50/60 Hz             |
| Frequency 4  | 50/60 Hz             | 50/60 Hz             | 50/60 Hz             |
| Phases   | 1/N/PE               | 1/N/PE               | 1/N/PE               |
| Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^\circ\text{C}$ )    | 1100 $\Omega$ cm     | 1100 $\Omega$ cm     | 1100 $\Omega$ cm     |
| Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25 \text{ }^\circ\text{C}$ )       | 1100 $\Omega$ cm     | 1100 $\Omega$ cm     | 1100 $\Omega$ cm     |
| Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^\circ\text{C}$ ) | 909 $\mu\text{S/cm}$ | 909 $\mu\text{S/cm}$ | 909 $\mu\text{S/cm}$ |
| Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25 \text{ }^\circ\text{C}$ )    | 909 $\mu\text{S/cm}$ | 909 $\mu\text{S/cm}$ | 909 $\mu\text{S/cm}$ |
| Height   | 143 mm               | 143 mm               | 143 mm               |
| Width  | 190 mm               | 190 mm               | 190 mm               |
| Depth  | 82 mm                | 82 mm                | 82 mm                |
| Water connection   | G 3/8 A              | G 3/8 A              | G 3/8 A              |
| ON   | > 1,0 l/min          | > 1.3 l/min          | > 2.6 l/min          |
| IP rating  | IP 25                | IP 25                | IP 25                |
| Colour   | white                | white                | white                |
| Weight   | 1.40 kg              | 1.40 kg              | 1.40 kg              |
| Energy efficiency class  |                      | A                    | A                    |

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.